

Page 1/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024 Version number 35 (replaces version 34) Revision: 06.05.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name MC-Injekt 2300 flow - Komponente B

· Article number: 3041

1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

· Application of the substance

/ the mixture Polyurethane resin

Injektion

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

nent: msds@mc-bauchemie.de

· 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.
Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP

regulation.

(Contd. on page 2)



Page 2/10

(Contd. of page 1)

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024 Version number 35 (replaces version 34) Revision: 06.05.2024

#### Trade name MC-Injekt 2300 flow - Komponente B

· Hazard pictograms

><

\_

· Signal word Danger

Hazard-determining

components of labelling: diphenylmethanediisocyanate, isomeres and homologues

· **Hazard statements** H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H317 May cause an allergic skin reaction. H351 Suspected of causing cancer. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated

exposure.

• Precautionary statements P260 Do not breathe dust/fume/gas/mist/vapours/

spray.

P280 Wear protective gloves/protective clothing/eye

protection/face protection/hearing protection.

P284 [In case of inadequate ventilation] wear

respiratory protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P342+P311 If experiencing respiratory symptoms: Call a

POISON CENTER/doctor.

P403+P233 Store in a well-ventilated place. Keep container

tightly closed.

• Additional information: EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before

industrial or professional use.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Active substance with propellant.

Mixture consisting of the following components.

(Contd. on page 3)



Page 3/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024 Version number 35 (replaces version 34) Revision: 06.05.2024

#### Trade name MC-Injekt 2300 flow - Komponente B

Dangerous compo	nents:	
CAS: 9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	30-60%
	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	
	Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 %	
	Skin Irrit. 2; H315: C ≥ 5 %	
	Resp. Sens. 1; H334: C ≥ 0.1 %	
	STOT SE 3; H335: C ≥ 5 %	
CAS: 108-32-7	Propylene carbonate	10-30%
EINECS: 203-572-1	Eye Irrit. 2, H319	
Additional informa	tion For the wording of the listed hazard phrases refer to section	on 16.

### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

• General information Immediately remove any clothing contaminated with the product.

Take affected persons into the open air.

Seek medical treatment.

· After inhalation Supply fresh air.

Call a doctor immediately.

After skin contact
 After eye contact
 Instantly wash with water and soap and rinse thoroughly.
 Rinse opened eye for several minutes under running water.

Seek medical treatment.

· After swallowing Call a doctor immediately.

## **SECTION 5: Firefighting measures**

· 5.1 Extinguishing media

· Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with

water jet or alcohol-resistant foam.

 5.2 Special hazards arising from the substance or

mixture

Can be released in case of fire

Carbon monoxide (CO) Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be

excluded, e.g.:

Hydrogen cyanide (HCN)

· 5.3 Advice for firefighters

· Protective equipment: Wear self-contained breathing apparatus.

GB



Page 4/10

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 06.05.2024 Printing date 26.05.2024 Version number 35 (replaces version 34)

Trade name MC-Injekt 2300 flow - Komponente B

(Contd. of page 3)

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures

Ensure adequate ventilation Use breathing protection against the effects of fumes/dust/aerosol.

· 6.2 Environmental

precautions:

Prevent material from reaching sewage system, holes and cellars.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe

Ensure good ventilation/exhaustion at the workplace. handling

Prevent formation of aerosols.

· Information about protection

against explosions and fires: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

Store only in the original container. storerooms and containers:

Information about storage in

one common storage facility: Store away from foodstuffs.

· Further information about

storage conditions: Keep container tightly sealed.

Storage class

### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL Short-term value: 0.07 mg/m<sup>3</sup>

Long-term value: 0.02 mg/m<sup>3</sup>

Sen; as -NCO

(Contd. on page 5)



Page 5/10

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 06.05.2024 Printing date 26.05.2024 Version number 35 (replaces version 34)

### Trade name MC-Injekt 2300 flow - Komponente B

(Contd. of page 4)

· DNELs

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

Inhalative DNEL 0.05 mg/m³ (ArL)

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

PNEC 1 mg/l (Sewage Treatment Plant)

0.1 mg/l (Mew) 1 mg/l (Freshwater)

PNEC 1 mg/kg dwt (Bod)

The lists that were valid during the compilation were used as basis. · Additional information:

· 8.2 Exposure controls Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

Keep away from foodstuffs, beverages and food. hygienic measures

Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin. Do not eat, drink or smoke while working.

Breathing equipment: Respiratory protection is required at inadequately ventilated

> workplaces and during spray processing. Fresh air masks or combination filters A2-P2 are recommended for short-term work.

· Hand protection Conditionally suitable materials for protective gloves; EN 374-3:

*Nitrile rubber - NBR: Thickness*  $\geq$  0.35mm.

Only suitable for splash protection. Only suitable for short-term exposure. In case of contamination, the protective gloves must be

changed immediately. Nitrile rubber, NBR

· Material of gloves

· Penetration time of glove

material

The exact breakthrough time must be obtained from the protective

glove manufacturer and must be observed.

· Eye/face protection

· Body protection:

Not required.

Protective work clothing.

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Dark brown · Smell: Characteristic

(Contd. on page 6)



Page 6/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024 Version number 35 (replaces version 34) Revision: 06.05.2024

#### Trade name MC-Injekt 2300 flow - Komponente B

(Contd. of page 5) Melting point/freezing point: Not determined Boiling point or initial boiling point and boiling range ° C (CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues) · Flash point: Not applicable · Auto-ignition temperature: 430 °C (CAS: 108-32-7 Propylene carbonate) Not determined. · pH · Viscosity: · Kinematic viscosity Not determined. · dynamic at 20 °C: 58 mPas · Solubility · Water: Hydrolized · Steam pressure at 20 °C: 0 hPa (CAS: 108-32-7 Propylene carbonate) · Density and/or relative density · Density at 20 °C 1.08 g/cm<sup>3</sup> · 9.2 Other information · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Self-inflammability: Product is not selfigniting. Explosive properties: Product is not explosive. · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Void · Pyrophoric solids Void · Self-heating substances and mixtures · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void



Page 7/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024 Version number 35 (replaces version 34) Revision: 06.05.2024

Trade name MC-Injekt 2300 flow - Komponente B

(Contd. of page 6)

### SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

**conditions to be avoided:** No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions Reacts with amines

• 10.4 Conditions to avoid No further relevant information available. • 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

### **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

CAS: 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues

Oral LD50 >10000 mg/kg (Rat)

 Dermal
 LD50
 >5000 mg/kg (Rab)

 Inhalative
 LC50/4 h
 ~450 mg/l (Rat)

 CAS: 108-32-7 Propylene carbonate

 Oral
 LD50
 >5000 mg/kg (rat)

 Dermal
 LD50
 >2000 mg/kg (rabbit)

• Skin corrosion/irritation Causes skin irritation.
• Serious eye damage/irritation Causes serious eye irritation.

· Respiratory or skin

sensitisation May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

May cause an allergic skin reaction.

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Suspected of causing cancer.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure May cause damage to organs through prolonged or repeated

exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

GB



Page 8/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024 Version number 35 (replaces version 34) Revision: 06.05.2024

Trade name MC-Injekt 2300 flow - Komponente B

(Contd. of page 7)

### **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

12.2 Persistence and

degradability No further relevant information available.

12.3 Bioaccumulative

potential
No further relevant information available.
12.4 Mobility in soil
No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Additional ecological information:

• General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

14.1 UN number or ID number		
· ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
· ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:		
Marine pollutant:	No	

(Contd. on page 9)



Page 9/10

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024 Version number 35 (replaces version 34) Revision: 06.05.2024

#### Trade name MC-Injekt 2300 flow - Komponente B

(Contd. of page 8)

· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk accord IMO instruments	<b>ling to</b> Not applicable.	
· UN "Model Regulation":	Void	

### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/ legislation specific for the

substance or mixture No further relevant information available.

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Relevant phrases H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 May cause respiratory irritation.H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or

repeated exposure.

EUH204 Contains isocyanates. May produce an allergic reaction.

· Department issuing data

**specification sheet:** Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)

(Contd. on page 10)



Page 10/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024 Version number 35 (replaces version 34) Revision: 06.05.2024

#### Trade name MC-Injekt 2300 flow - Komponente B

(Contd. of page 9)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

\* \* Data compared to the previous version altered.

GB